



Description:

Firetech WB Paint is designed to make your existing walls, wooden structure, metal, etc flame resistant. It is most feasible and up to date product developed to protect wall, wood, etc from fire just by easily top coating present surface. It is a water base Fire retardant coating that has been developed using latest research work and technologies. Firetech WB Paint molecules permeates into holes instantly to make surface flame retardant and imparts properties which resists spread of flame. Flame dies out itself due to its unique self extinguishing properties. In the presence of heat or flame, a reaction forms a thick sponge like cellulose layer upon a heated surface which has considerable insulating value. Thus retarding the spread of flame. Its revolutionary technology saves on precious life and properties. It is a protection for wall, Wood, Timber, etc against collapse. It can be made available in different colors as per requirement.

Features

- Excellent flame resistance property
- Economical
- Clear coating
- Different colors available
- Easy Cleaning
- Controls surface spread of flame
- Easy to use
- Flames die out by itself due to unique self extinguishes properties
- Provides fire resistance barrier on a variety of substrates
- Old material becomes fireproof easily

Area of Application:

It is most ideal for fire protection of walls, wooden, metal, etc. It is a must to increase life and fire resistance property of the surface on which it is quoted.

- Product Characteristics:
- Type - Liquid
- Color and finish –Color as per requirement
- Thinning – Can be done with water as required
- Shell life - 1 year

Method of application:

- Brush / Spray /Roller
- Finish
- Perfect paint finish
- Drying time
- Surface drying -4-6 hours
- Hard drying -12-24 hours
- Recoating –after 24 hours
- Full cure – 10-12 days as per weather conditions

Surface Preparation:

All surfaces to be painted must be clean and used as per good painting practise.

Coverage:

50-60 sq feet per ltr per coat as per the surface

Priming:

Not Required

Shades:

White, Ivory , Green , Customized colors available

Shelf Life:

12 months (sealed)

Packing:

20L , 4L

Cleaning:

Clean all the painting equipment with water after use

Precautions:

- Store in cool and dry place.
- Do not apply when ambient temperature is less than 10C and more than 45C.

Stir well before use

Note:

Application procedure of material is behind our control , We do not take any responsibility of safety , suitability and results of product after application. It is advisable to sample check product before its application.

